



# TR Model

## **TP Series**

# Recessed Panel LED 2x2 (Dimmable)

Smooth and uniform light across the entire panel of the luminaire provides visual comfort.

## **Product Specifications**

#### **FEATURES & BENEFITS:**

- Modern and clean style, no exposed fasteners.
- Direct replacement of 2'x2' fluorenscent trouffer luminaire.
- Excellent luminaire efficacy provides significant energy saving.
- Smooth edge for easy handling.
- Dimmable via 0-10VDC standard
- Available in 3000K, 3500K, 4000K, 5000K color temperature.
- Rated Life: 50,000 hours
- Assembled in USA with domestic and imported components
- RoHS Compliant Mercury free and Lead free

### **Applications:**

- Shop lighting
- Commercial lighting
- Boutique lighting
- Illumination lighting
- Architectural lighting

**Lumen Output:** 35W -3000K: 3208 lumen

35W -5000K : 3401 lumen 40W -3000K : 3552 lumen 40W -5000K : 3848 lumen

**Operating Temperature:** -4 F to 104 F (-20 to 40 C)

**Color Temperature (TYP):** 3000K, 3500K, 4000K & 5000K

Color Rendering Index (CRI): 80

Ordering Information Example: TR224040TPG

R224040TPG

#### **Electrical System:**

All electrical components are UL certified.

**Input Voltage:** 120/277VAC **Power Consumption:** 35W, 40W

#### **Construction / Finish**

- 24 guage die formed cold-rolled steel body.
- No exposed fastners.
- Smooth edge for easy handling.
- Simple latch locking system to secure the diffuser or lens.

#### Warranty

Five-year limited warranty.





Model Number		Luminaire Type	Color Temperature	Output Wattage	Luminaire Style	Installation	
	TR	22	40	40	TP	<b>G</b> (Optional)	
		<b>22-</b> 2'x2'	<b>30-</b> 3000K <b>35-</b> 3500K <b>40-</b> 4000K <b>50-</b> 5000K	<b>35-</b> 35W <b>40</b> - 40W	TP- Recessed Panel	G- Standard Lay-in Grid T- Concealed T S- Slot Grid F- Flange Trim with supporting swing Gates	


**Note:** Specifications subject to change without notice. Actual performance may differ as a result of end user environment and application.

Rev 1 - 03/02/15 Page 1 of 2





## **Dimensions:**



Length - 23-3/4" Width - 23-3/4" Depth - 3-3/8"

## **Installatioin Method**

<b>G</b> Grid/Lay-in Standard	<b>G</b> Concealed T	<b>G</b> Slot Grid	<b>F</b> Flange Trim With Supporting Swing Gates	Ceiling Type Exposed Grid Concealed T Slot Grid Flange	Trim Type G G G G

When order Flange Kit for installation in drywall ceiling, please consult us for compatibility.

I F D O RITE

Rev 1 - 03/02/15 Page 2 of 2