

16,000 + Lumens

Wall Mount
Dimensions: 8.384x5.484x3.523in.



ENHANCED LED PERFORMANCE IN A CLASSIC DESIGN

The LED wall mount offer maximum light output for general purpose area and security lighting. They efficiently deliver lumens, and consume less energy than traditional wall mount technologies.

This versatile luminaire is ideal for replacing existing MH fixtures.

APPLICATIONS: Security, entry ways, stairways, storage and perimeter areas, as well as residential exteriors.

WALL MOUNT

SKU	WM15W12V50KD
LIGHT OUTPUT	1,600 Lumens
COLOR TEMP	5000K
POWER CONSUMPTION	15W
COLOR ACCURACY	82CRI
REPLACES	100W INCANDESCENT
PRICE	

2,200 + Lumens

Wall Mount
Dimensions: 8.384x5.484x3.523in.



WALL MOUNT

SKU	WM17W27V50KD	WM25W27V50KD
LIGHT OUTPUT	1,700 Lumens	2,200 Lumens
COLOR TEMP	5000K	5000K
POWER CONSUMPTION	17W	25W
COLOR ACCURACY	82CRI	82CRI
REPLACES	120W INCANDESCENT	50W HID
PRICE		



Accessories



Photocell - Button, 120V/208V/240V/277V

USE: Photocell is field installed
or Pre-installed in factory by requesting

UL LISTING

UL listed for wet location.

DESIGNLIGHTS CONSORTIUM

DLC qualified at 4000K and 5000K.

LEDs

LM-80 certified high performance and reliable Lumileds LEDs.

DRIVERS

Tailored constant-current Led power supply, UL class 2.

HOUSING AND FINISH

Die-cast aluminum with durable dark bronze/black/white coat finish.

INSTALLATION

Outlet box or wall mounted directly.

AMBIENT TEMPERATURE

Suitable for use in -25 °C to 40 °C.

WARRANTY

5 years limited warranty.