

MF Model

LED Mini Floodlight Fixture



Product Specifications

FEATURES & BENEFITS:

- Design for damp and wet locations.
- Excellent luminaire efficacy provides significant energy saving.
- Resistance to corrosion, flame, and vandalism.
- Available in 4000K & 5000K color temperature.
- Rated Life : >=50,000 hours
- RoHS Compliant - Mercury free and Lead free

Lumen Output : 15W- 1500 lm
30W- 3000 lm

Operating Temperature: -13F to 104 F (-25 to 40 C)

Color Temperature (TYP): 4000K & 5000K

Color Rendering Index (CRI): >=70

Power Factor (PF): >=0.9

Electrical System:

All electrical components are UL certified.

Input Voltage: 120/277VAC

Power Consumption: 15W and 30W

Construction /Finish

- Aluminium housing
- Color : Black/Dark Bronze
- Size : 4.72"x 2.95"x 1.27"

Warranty

Five-year warranty.

Ordering Information

Example: **MF3012050KBB**



Model Number	Luminaire Type	Beam Angle	Color Temperature	Fixture Color	Mounting Method
MF	30	120	50K	B	B
	15 - 15W 30 - 30W	120 - 120°	40K - 4000K 50K - 5000K	B - Black DB - Dark Bronze	2 - 1/2" knuckle B - Bracket

Note: Specifications subject to change without notice. Actual performance may differ as a result of end user environment and application.